

# NITE C# Wrappers - Programmer's Guide

March, 2011

**COPYRIGHT © 2011 PrimeSense™ Inc.**

ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY REPRODUCED, PHOTOCOPIED, STORED ON A RETRIEVAL SYSTEM OR TRANSMITTED WITHOUT THE EXPRESS PRIOR WRITTEN PERMISSION OF PRIMESENSE IN

# About This Document

This document describes the .NET C# wrappers for PrimeSense's NITE Middleware and for OpenNI.

PrimeSense Confidential

# Table of Contents

|          |                                 |          |
|----------|---------------------------------|----------|
| <b>1</b> | <b>GENERAL .....</b>            | <b>4</b> |
| 1.1      | OBJECTS .....                   | 4        |
| 1.1.1    | <i>MessageGenerator</i> .....   | 4        |
| 1.1.2    | <i>MessageListener</i> .....    | 4        |
| 1.1.3    | <i>SessionGenerator</i> .....   | 4        |
| 1.1.4    | <i>SessionManager</i> .....     | 4        |
| 1.1.5    | <i>Broadcaster</i> .....        | 4        |
| 1.1.6    | <i>FlowRouter</i> .....         | 5        |
| 1.1.7    | <i>PointControl</i> .....       | 5        |
| 1.1.8    | <i>PointFilter</i> .....        | 5        |
| 1.1.9    | <i>PointDenoiser</i> .....      | 5        |
| 1.1.10   | <i>PointArea</i> .....          | 5        |
| 1.1.11   | <i>CircleDetector</i> .....     | 5        |
| 1.1.12   | <i>PushDetector</i> .....       | 6        |
| 1.1.13   | <i>SteadyDetector</i> .....     | 6        |
| 1.1.14   | <i>SwipeDetector</i> .....      | 6        |
| 1.1.15   | <i>WaveDetector</i> .....       | 6        |
| 1.1.16   | <i>SelectableSlider1D</i> ..... | 6        |
| 1.1.17   | <i>SelectableSlider2D</i> ..... | 7        |

# 1 General

XnVNITE.net - The C# wrapper for NITE covers most of the APIs available in the C++ API of NITE. All the .Net objects mirror C++ objects (and indeed wrap specific objects). The C++ object has the same name, with the XnV prefix (whereas the C# API is in the NITE namespace). Please refer to NITE user guides and NITE API reference guides for detailed description.

## 1.1 Objects

### 1.1.1 MessageGenerator

This is a general generator, mirroring XnVMessageGenerator. It exports APIs to Add and Remove listeners, as well as to generate a message (IntPtr). See XnVMessageGenerator's documentation in the API reference for more information.

### 1.1.2 MessageListener

This is a general listener, mirroring XnVMessageListener. It exports APIs to parse a message (IntPtr), and has an event when a message is parsed, as well as when the listener is activated or deactivated. See XnVMessageListener's documentation in the API reference for more information.

### 1.1.3 SessionGenerator

This is a general session generator, mirroring XnVSessionGenerator. It exports APIs for the following events: SessionStart, SessionEnd and FocusProgress. It also exports APIs to start tracking at a specific point, and to lose a specific point or all points. A SessionGenerator is a MessageGenerator. See XnVSessionGenerator's documentation in the API reference for more information.

### 1.1.4 SessionManager

This is an object mirroring XnVSessionManager. It exports initialization and management of the gestures that start sessions or revive sessions as quick refocus gestures. A SessionManager is a SessionGenerator. See XnVSessionManager's documentation in the API reference for more information.

### 1.1.5 Broadcaster

This is an object mirroring XnVBroadcaster. It passes messages it receives to all the listeners that registered to it. A Broadcaster is a MessageListener as well as a MessageGenerator (through IMessageGenerator). See XnVBroadcaster's documentation in the API reference for more information.

### 1.1.6 FlowRouter

This is an object mirroring XnVFlowRouter. It passes messages it receives to a single 'active' listener. It also generates activation/deactivation messages when the 'active' listener is changed. A FlowRouter is a MessageListener.

See XnVFlowRouter's documentation in the API reference for more information

### 1.1.7 PointControl

This is a general listener for point messages. It mirrors XnVPointControl.

PointControl gets the hand points from the messages, and allows inheriting objects to parse the points. A PointControl is a MessageListener.

See XnVPointControl's documentation in the API reference for more information.

### 1.1.8 PointFilter

This is a general filter for point messages. It mirrors XnVPointFilter.

This is a base class for all filters of point messages. A PointFilter is a PointControl as well as a MessageGenerator (through IMessageGenerator).

See XnVPointFilter's documentation in the API reference for more information.

### 1.1.9 PointDenoiser

This is a point filter that smoothes existing points. It mirrors XnVPointDenoiser.

It receives a point message, and generates a different point message, with a smoothed point. A PointDenoiser is a PointFilter.

See XnVPointDenoiser's documentation in the API reference for more information.

### 1.1.10 PointArea

This is a point filter that hides points that reside outside of a specific predefined area. It mirrors XnVPointArea. It receives a point message, and passes through only the points within the specific area declared. As far as the point filters/controls downstream, these points don't exist (meaning they get PointDestroy if they ever saw them, etc.). A PointArea is a PointFilter.

See XnVPointArea's documentation in the API reference for more information.

### 1.1.11 CircleDetector

This is a point control that understands points of the primary hand as circular movements. It mirrors XnVCircleDetector. It exports events of CircleDetected (available every frame when a circle is alive), and NoCircle (when a circle is lost). A CircleDetector is a PointControl.

See XnVCircleDetector's documentation in the API reference for more information.

### 1.1.12 PushDetector

This is a point control that understands points of the primary hand as push movements (movement along the Z-axis). It mirrors XnVPushDetector.

It exports events for PushDetected (when a movement forward along the Z-axis is detected) and Stabilized (when no movement is detected after a push). A PushDetector is a PointControl.

See XnVPushDetector's documentation in the API reference for more information.

### 1.1.13 SteadyDetector

This is a point control that looks for when a hand point is steady (variance under a certain threshold). It exports events for Steady (when the variance of a hand that isn't steady is under a threshold for the first time) and NotSteady (when the variance of a hand that is steady is over a threshold for the first time). A SteadyDetector is a PointControl.

See XnVSteadyDetector's documentation in the API reference for more information.

### 1.1.14 SwipeDetector

This is a point control that looks for swipe movements of the primary hand along either the Y-axis or the X-axis. It exports events for Swipe in either of the 4 directions, and an event for a general swipe (with the direction as a parameter). A SwipeDetector is a PointControl.

See XnVSwipeDetector's documentation in the API reference for more information.

### 1.1.15 WaveDetector

This is a point control that looks for a wave movement of the primary hand. The definition of wave is supplied by the parameters. It exports an event for when a wave is detected. A WaveDetector is a PointControl.

See XnVWaveDetector's documentation in the API reference for more information.

### 1.1.16 SelectableSlider1D

This is a point control that uses the primary hand to represent a slider along either the X, Y or Z axes. The slider's size is determined by configuration, and then the position of the hand is available as a number between 0 and 1 (the ValueChange event). The slider is also split into a certain number of cells, each called an Item. When the hand changes position to be in a different Item, the ItemHover event is raised. When a selection is performed (movement along any of the other axes) the ItemSelected event is raised. A SelectableSlider1D is a PointControl.

See XnVSelectableSlider1D's documentation in the API reference for more information.

### 1.1.17 **SelectableSlider2D**

This is a point control that uses the primary hand to represent a 2D slider on the X/Y plane. The slider's sizes in both axes are determined by configuration, and then the position of the primary hand is available as a number between 0 and 1 for each axis (the ValueChange event). The slider is also split into a number of cells for each axis ( $n*m$ ), each called an Item. When the hand changes position to be in a different Item, the ItemHover event is raised. When a selection is performed (movement in the Z-axis) the ItemSelected event is raised. A SelectableSlider2D is a PointControl.

See XnVSelectableSlider2D's documentation in the API reference for more information.